



Rottweg 17 • D 48683 Ahaus
Tel. (0 25 61) 93 84-0
Fax (0 25 61) 93 84 36
Internet: www.ab-maschinen.de
E-Mail: info@ab-maschinen.de

Schweißtechnik
Lagereinrichtungen
Industriebedarf
Werksvertretungen
Gebrauchtmaschinen

ABUS Säulenschwenkkran LS (1008-8531778)



Control type
konventionell

Machine no.
1008-8531778

Make
ABUS

Location
Ahaus

Description:

- Load capacity 250 kg
- projection 4000 mm
- Construction height 4025 mm
- Crane lacquer in color RAL 1007 daffodil yellow
- Calculation basis DIN 15018
- Crane classification H2 / B2
- Operating location hall operation
- Size / bracket profile LS36 / FormC 110x90
- Height of the lower edge of the boom 3425 mm
- Operating voltage 3 / PE ~ 50 Hz 400 V
- Direct control type of control
- Degree of protection IP55
- Swivel range, nominally 270 °
- Panning by hand

including:

- Anchor rods size LS 36
- Consists of 8 pieces M24 mm x 800 mm, with 1 steel template (420/8) for
- Fastening to the foundation, including accessories

Electric chain hoist:

- Chain hoist type GM 2 250.6-1, 1-leg
- painted in color RAL 5017
- traffic blue
- Load capacity 250 kg
- hook path 4000 mm
- highest hook position 3034 mm
- Calculation basis FEM 9.901
- Drive group 2m / M5
- Lifting, 2-stage (pole switchable) 1.5 / 6 m / min
- Lifting power 0.09 / 0.35 kW
- duty cycle 60% ED

** Fig. Shows a similar crane system

Machine attributes

weight max. in kg:	250 kg
arm length:	4000 mm
height:	3425 Unterkante Ausleger
total column height:	4.025 mm
swivelling range:	270 Grad
Total weight, approx.:	375 kg

Machine images

