



Rottweg 17 • D 48683 Ahaus  
Tel. (0 25 61) 93 84-0  
Fax (0 25 61) 93 84 36  
Internet: [www.ab-maschinen.de](http://www.ab-maschinen.de)  
E-Mail: [info@ab-maschinen.de](mailto:info@ab-maschinen.de)

Schweißtechnik  
Lagereinrichtungen  
Industriebedarf  
Werksvertretungen  
Gebrauchtmaschinen

## ALPMAC B175-3100 (1008-8308163)



**Control type**  
CNC

**Construction year**  
2025

**Machine no.**  
1008-8308163

**Make**  
ALPMAC

**Location**  
Ahaus

\*\* Demonstration/demo machine (!!)  
\*\* from our exhibition (like NEW)  
\*\* with very few operating hours

ALPMAC manufacturer video:

[https://www.youtube.com/watch?v=\\_FxYyPAcxIE](https://www.youtube.com/watch?v=_FxYyPAcxIE)

[https://www.youtube.com/watch?v=YfkX9RwWv\\_0](https://www.youtube.com/watch?v=YfkX9RwWv_0)

ALPMAC product video Model B:

<https://www.youtube.com/watch?v=lmT1tfy43WE>

MODEL SERIES B175-3100 - CNC electro-hydraulic press brake with:

- \* increased installation height
- \* increased cylinder stroke
- \* increased projection

! MANUFACTURED FROM CERTIFIED QUALITY STEEL (ST 37-42-52)

- ! HIGH PERFORMANCE HYDRAULIC COMPONENTS (HAWE GERMANY)
- ! SMOOTH RUNNING DUE TO LESS OPERATING PRESSURE (50-60 DB)
- ! INDUCTION HARDENED & CHROME-PLATED CYLINDER PISTONS FOR CONTINUOUS USE
- ! BACK STOP COMPONENTS MADE FROM CAST ALUMINUM
- ! BACK STOP WITH POWERFUL DRIVE MOTOR (1.0 KW)
- ! MACHINE TABLE MADE OF ROBUST & RESISTANT STEEL (C45)

Equipment:

- CNC electro-hydraulic press brake
- DELEM CNC control model "DA-58T" graphics/touchscreen
- \* 2D graphic programming
- \* 15" color TFT screen with high resolution
- \* Bending sequence calculation
- \* Product programming and display in real size
- \* USB interface
- CNC controlled axis: Y1 - Y2 - X - R - crowning
- CNC electro-motorized back stop (X axis)
- \* on ball screws
- \* Travel path .. max. 750 mm
- \* Travel speed X axis .. 350 mm/s
- \* with 2x manually adjustable stop fingers
- CNC electro-motorized height adjustment (R axis)
- \* Travel path .. max. 250 mm
- CNC electro-motorized Table crowning
- ROLLERI Rehfuß upper tool "PS 135.85-R08", system "A"
- \* including quick-change clamping
- \* including crowning device in the tool holder
- ROLLERI split universal die block "M 460 R"
- \* including 1x die shoe "C 1050-R"
- Safety device at the rear: light barrier
- HAWE hydraulic components
- FIESSLER AKAS laser protection device in front of the machine (incl. FPSC)
- 2x front support arms with SLIDING system
- \* easy and keyless height adjustment
- FIESSLER freely movable double foot control
- CE mark / declaration of conformity

## Machine attributes

pressure:	175 t
chamfer lenght:	3100 mm
distance between columns:	2600 mm
column arm:	410 mm
ram stroke speed:	160 mm/sec
work speed:	10.0 mm/sec
return speed:	120 mm/sec
work stroke:	265 mm
daylighth:	480 mm
table height:	900 mm
table width:	90.0 mm
oil volume:	230 ltr.
voltage:	400 Volt
total power requirement:	18.5 kW
weight:	10500 kg
range L-W-H:	4100 x 2000 x 2820 mm

## Machine images