



Rottweg 17 • D 48683 Ahaus  
Tel. (0 25 61) 93 84-0  
Fax (0 25 61) 93 84 36  
Internet: www.ab-maschinen.de  
E-Mail: info@ab-maschinen.de

Schweißtechnik  
Lagereinrichtungen  
Industriebedarf  
Werksvertretungen  
Gebrauchtmaschinen

## ALZMETALL ALZSTAR 40 iTRONIC-V (1008-8100653)



**Control type**  
konventionell

**Machine no.**  
1008-8100653

**Make**  
ALZMETALL

**Location**  
Ahaus

**\*\* NEW ALZMETALL MODEL RANGE \*\***

7" TFT - LCD display with touch function:

- \* Spindle speed setpoint
- \* Actual speed display
- \* Integrated drilling depth display
- \* with touch zero point transfer
- \* Virtual drilling depth scale in the display
- \* Machine status displays and warnings in the display
- \* Service information
- \* Selectable user language: DE / EN / FR / ES / IT / NL / RU.

Furnishing:

- Infinitely variable speed setting by means of an adjusting lever
- automatic spindle feed with feed overload protection
- Spindle protection with electrical fuse
- Three separate buttons for clockwise rotation - counterclockwise rotation -

stop

- Mushroom pushbutton (latching) for EMERGENCY STOP
- Main switch, lockable
- Right and left rotation by contactor control
- Control voltage 24 volts
- Protection class IP 54
- Painting: DD textured paint, signal white RAL 9003 PANTONE 7545c, black

including special accessories:

- 25. Coolant system B.

## Machine attributes

bore capacity in steel (diameter):	40.0 mm
throat:	293 mm
bore stroke:	120 mm
morse taper:	3 MK
table::	515 x 360 mm
turning speeds:	160 - 2250 U/min
column diameter:	115 mm
feed:	0.10 + 0.20 mm/U
T-slots:	2 x 14 x 224 mm
distance spindle /table:	117 / 701 mm
engine output:	1.45 / 1.90 kW
weight:	285 kg
Machine height:	1840 mm

## Machine images





Rottweg 17 • D 48683 Ahaus  
Tel. (0 25 61) 93 84-0  
Fax (0 25 61) 93 84 36  
Internet: [www.ab-maschinen.de](http://www.ab-maschinen.de)  
E-Mail: [info@ab-maschinen.de](mailto:info@ab-maschinen.de)

Schweißtechnik  
Lagereinrichtungen  
Industriebedarf  
Werkvertretungen  
Gebrauchtmaschinen

