



Rottweg 17 • D 48683 Ahaus
Tel. (0 25 61) 93 84-0
Fax (0 25 61) 93 84 36
Internet: www.ab-maschinen.de
E-Mail: info@ab-maschinen.de

Schweißtechnik
Lagereinrichtungen
Industriebedarf
Werksvertretungen
Gebrauchtmaschinen

BERG & SCHMID GBS 242 DG AutoCut (1008-8170062)

© A + B Werkzeuge Maschinen Handels GmbH



Control type
konventionell

Machine no.
1008-8170062

Make
BERG & SCHMID

Location
Ahaus

Equipment:

- compact / robust manual band saw (INDUSTRY)
- * for sawing solid material and profiles
- ball bearing support table for miter cuts left 60° to right 45°
- * durable + easy miter adjustment
- 2x selectable cutting speeds (37 + 74 m/min.)
- continuously adjustable saw frame feed
- automatic shutdown at the end of the cut
- manually adjustable quick-release vice
- * including quick-release lever
- machine base including built-in automatic cooling
- electrical display and monitoring of the machine
- operating instructions

BERG SCHMID Auto-Cut system = 3-stage system

1. automatic lowering & automatic saw cut
2. manual operation - lowering + saw cut















3. high-speed lowering of the saw frame - without saw cut

Machine attributes

cutting diameter:	250 mm
capacity 90 degrees: square:	210 x 210 mm
capacity 90 degrees: flat:	290 x 210 mm
capacity 45 degrees: round:	220 mm
capacity 45 degrees: flat:	210 x 200 mm
capacity 45 degrees: square:	200 x 200 mm
capacity 60 degrees: round:	140 mm
capacity 60 degrees: square:	130 x 130 mm
capacity 60 degrees: flat:	140 x 130 mm
dimensions of saw-band:	2965 x 27 x 0,9 mm
cutting speed:	35 + 70 m/min
work height max.:	940 mm
total power requirement:	1,1 / 1,3 kW
weight of the machine ca.:	290 kg.
range L-W-H:	1250 x 1500 x 1700 mm

Machine images

© A + B Werkzeuge Maschinen Handels GmbH

									Best. Nr.
 90°	250	210	290 x 210	400 V 1,1 / 1,3	H 27	290		35 + 70	20 346
 45° fl.	220	200	210 x 200		≤ 0,9		B 1.250	25 – 90	20 347
 60° fl.	140	130	140 x 130		L 2.965		L 1.500		
 45° re.	170	170	170 x 170				H 1.700 h 940		